

Sure - Clamp Access Specifications

- A. General : **Fabricate round access section with liner** suitable for duct pressure class. Clamping type, removable ductwork section with draw latch.
- B. Provide : Sure Clamp access size as indicated on drawings.
- C. Size : 22" maximum diameter
- D. Material : Galvanized ASTM A527
- E. Flange Connection : 90 degree continuous machine formed flange.
- F. Seams : (RL-3) Lap and spot weld on 2" interval
- G. Access Section : Galvanized sheet metal construction , 22 Gauge 4" to 12" diameter, 20 Gauge 13" to 22" diameter.
- H. Insulation : 1/2" Armaflex internally lined. Top surface even and on the same plane with adjoining ductwork.
- I. Clamps : 20 gauge galvanized with zinc coated draw latch and self centering flange guides. Gasket profile forms to the inside of clamp and seals the outer edges of the ductwork flange.
- J. Gasket : Red silicone sponge gasket. Temperature range - 40F to +400 F
- K. Seal seams in accordance with SMACNA HVAC Duct Construction Standard - Metal and Flexible.
- L. Manufacturer :

Langdon Inc.
9865 Wayne Ave Cincinnati, Ohio 45215
Phone (513)733-5955 ext.238 Fax (513)733-8050
www.langdonsheetmetal.com
Attn. : Joe Sandman. Mobile # 513-678-6825

Sure-Clamp Access